

# Comparison of Penetration Efficiency in Axial and Planer Symmetries

*Y. Partom  
Institute for Advanced Technology  
The University of Texas at Austin*


*November 1993*

19960913 067

*IAT.R 0033*

Approved for public release; distribution unlimited.

# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

## ***Certification of Technical Review***

Yehuda Partom 3/23/94  
Yehuda Partom

Stephan Bless 3/31/94  
Stephan Bless

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB NO. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

|   |  |   |  |
|---|--|---|--|
| 1. AGENCY USE ONLY (Leave blank)  |  | 2. REPORT DATE<br>November 1993                         | 3. REPORT TYPE AND DATES COVERED<br>Technical Report   |
| 4. TITLE AND SUBTITLE<br>Comparison of Penetration Efficiency in Axial and Planer Symmetries  |  |   | 5. FUNDING NUMBERS<br>Contract # DAAA21-93-C-0101      |
| 6. AUTHOR(S)<br>Y. Partom   |  |   |  |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br>Institute for Advanced Technology<br>The University of Texas at Austin<br>4030-2 W. Braker Lane, #200<br>Austin, TX 78759   |  |   | 8. PERFORMING ORGANIZATION REPORT NUMBER<br>IAT.R 0033 |
| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>U.S. Army Research Laboratory<br>ATTN: AMSRL-WT-T<br>Aberdeen Proving Ground, MD 21005-5066  |  |   | 10. SPONSORING / MONITORING AGENCY REPORT NUMBER       |
| 11. SUPPLEMENTARY NOTES<br>The view, opinions and/or findings contained in this report are those of the author(s) and should not be considered as an official Department of the Army position, policy, or decision, unless so designated by other documentation.  |  |   |  |
| 12a. DISTRIBUTION / AVAILABILITY STATEMENT<br>Approved for public release; distribution unlimited.  |  |   | 12b. DISTRIBUTION CODE<br>A                            |
| 13. ABSTRACT (Maximum 200 words)<br>It has been known for some time that, for a given target, a flat cross section projectile would penetrate deeper than a circular cross section projectile, other factors being equal. This invoked the idea that a cruciform cross section projectile would have an advantage over the circular cross section projectile. We used AUTODYN2D to simulate penetration of steel and tungsten alloy projectiles into steel targets for axial and planar symmetries. The purpose was to see to what extent the planar projectiles have an advantage over circular projectiles. We found that: planar projectiles penetrate more than circular projectiles at low velocities (1.5 km/s); planar projectiles lose their advantage with increasing velocity; much larger target dimensions are needed for full confinement of planar projectiles; and craters created by planar projectiles are much wider and their width is not constant. |  |   |  |
| 14. SUBJECT TERMS<br>axial symmetries, planer symmetries, penetration efficiency, planar projectiles  |  |   | 15. NUMBER OF PAGES<br>147                             |
|   |  |   | 16. PRICE CODE   |
| 17. SECURITY CLASSIFICATION OF REPORT<br>Unclassified   | 18. SECURITY CLASSIFICATION OF THIS PAGE<br>Unclassified | 19. SECURITY CLASSIFICATION OF ABSTRACT<br>Unclassified | 20. LIMITATION OF ABSTRACT<br>UL                       |

# Comparison of Penetration Efficiency in Axial and Planer Symmetries

by  
Yehuda Partom

It has been known for some time that, for a given target, a flat cross section projectile would penetrate deeper than a circular cross section projectile, other factors being equal. This invoked the idea that a cruciform cross section projectile would have an advantage over the circular cross section projectile.

To simulate the penetration process of a cruciform projectile, we need to employ a 3D wavecode. As such a code is not yet available to us, we conducted a preparatory investigation using the 2D wavecode AUTODYN2D. We ran identical penetration problems in axial and planar (2D strain) symmetries. The planar symmetry projectile can be regarded as an extreme case of a flat projectile. This means that if indeed a flat projectile is more efficient than a circular projectile, the flat projectile (being laterally finite) always penetrates less than the equivalent planar symmetry projectile. Therefore, the basic idea of the investigation is as follows. If the simulations show that a planar symmetry projectile has sufficient advantage over the equivalent axial symmetry projectile, then a cruciform projectile may be a promising design.

In all simulations we used a steel target and steel or tungsten alloy  $L/D = 10$  projectiles. We used a Mie-Gruneisen EOS referenced to the shock adiabat with the parameters listed in Table 1 below:

Table 1  
EOS Parameters

|            | Steel            | Tungsten Alloy |
|------------|------------------|----------------|
| $\rho_0$   | 7.85 g/cc        | 17.3 g/cc      |
| $C_0$      | 3.57 mm/ $\mu$ s | 4.03           |
| $S$        | 1.92             | 1.24           |
| $\Gamma_0$ | 1.7              | 1.7            |
| $P_{min}$  | -2 GPa           | -2 GPa         |

where  $\rho$  = density,  $C_0$ ,  $S$  are the shock velocity particle velocity relation parameters,  $\Gamma_0$  = Gruneisen parameter and  $P_{min}$  is the spall strength.

For the stress deviator we used a constant shear modulus  $G$  and a von Mises yield surface with a constant flow stress  $Y$  as shown in Table 2:

Table 2  
Shear Stress Parameters

|     | Steel  | Tungsten Alloy |
|-----|--------|----------------|
| $G$ | 80 GPa | 140 GPa        |
| $Y$ | 1 GPa  | 2 GPa          |

Projectile dimensions were  $D/2 = 5$  mm,  $L = 100$  mm; the Euler cell dimensions were  $1 \times 1$  mm. Target dimensions varied according to symmetry, projectile material (steel or Tungsten alloy) and velocity. Specifically, in the planar symmetry case, we observed that very large target dimensions are needed to exert a reasonable amount of confinement. Target dimensions used in the various cases are listed in Table 3.


Table 3  
Target Dimensions

| No. | Projectile Material | Symmetry | Velocity (km/s) | $D_t/2$ (mm) | $L_t$ (mm) |
|-----|---------------------|----------|-----------------|--------------|------------|
| 1   | Steel               | Circular | 1.5             | 100          | 100        |
| 2   | "                   | "        | 2.0             | 100          | 200        |
| 3   | "                   | "        | 2.5             | 100          | 200        |
| 4   | "                   | planar   | 1.5             | 250          | 250        |
| 5   | "                   | "        | 2.0             | 280          | 280        |
| 6   | "                   | "        | 2.5             | 280          | 280        |
| 7   | tungsten alloy      | circular | 1.5             | 100          | 150        |
| 8   | "                   | planar   | 1.5             | 280          | 280        |


In the axial symmetry runs, cell dimensions in the target were also  $1 \times 1$  mm. In the planar symmetry runs, cell dimensions were  $1 \times 1$  mm for  $x < 100$  mm and  $y < 100$  mm, where  $x = 0$  is the impact surface and  $y = 0$  is the (planar) symmetry axis. Beyond  $x = 100$  mm and

$y = 100$  mm, cell dimensions grew progressively. There were 8 runs as shown in Table 3. The initial plan included 6 runs: 2 projectile materials (steel and tungsten alloy), 2 velocities (1.5 and 2.5 km/s (only for the steel projectile), and 2 symmetries (axial and planar); however, the higher velocity runs provided an unexpected result. To convince ourselves that there was no error, we did 2 additional runs with the steel projectile at an intermediate velocity (2 km/s). To document the runs we show plots of material status and velocity vectors (near the projectile target interface) in Appendix A (included only in 2 copies of this report). The plots are snapshots every 200 cycles. They are arranged according to the run numbers in Table 3. To analyze the results of these runs, we show interface velocity and projectile tail velocity history plots and penetration-erosion curves.


The velocity plots are shown in Figs. 1.1 to 1.4.




**Fig. 1.1.** Runs 1 and 4.



**Fig. 1.2.** Runs 2 and 5.




**Fig. 1.3.** Runs 3 and 6.




**Fig. 1.4.** Runs 7 and 8.

**Figure 1.1 to 1.4** Interface velocity and projectile tail velocity histories (1.1 is for runs 1 and 2, 1.2 is for runs 3 and 5, 1.3 is for runs 4 and 6, and 1.4 is for runs 7 and 8).


Figs. 1.1 and 1.4 are for  $V = 1.5$  km/s for steel into steel and for tungsten alloy into steel respectively. In both figures, we see that the penetration velocity for planar symmetry is high. This is not the case for  $V = 2$  km/s and  $V = 2.5$  km/s. In Fig. 1.2 ( $V = 2$  km/s, steel into steel), we see that the penetration velocities for planar and axial symmetries are about equal. In Fig. 1.3 ( $V = 2.5$  km/s, steel into steel), we see that the penetration velocity for planar symmetry is high than that for axial symmetry. This shows that a planar symmetry projectile has an advantage at low velocities but loses its advantage with increasing velocity. We see this behavior even more clearly in the penetration-erosion curves shown in Figs. 2.1 to 2.4.




**Fig. 2.1.** Runs 1 and 4.



**Fig. 2.2.** Runs 2 and 5.



**Fig. 2.3.** Runs 3 and 6.



**Fig. 2.4.** Runs 7 and 8.

**Figs. 2.1 to 2.4.** Penetration-erosion curves (2.1 is for runs 1 and 4, 2.2 is for runs 2 and 5, 2.3 is for runs 3 and 6, and 2.4 is for runs 7 and 8).

Figs 2.1 and 2.4 are for  $V = 1.5$  km/s, for steel into steel and tungsten alloy into steel, respectively. We see that in both cases, the planar symmetry projectile has about 30% advantage over the axial symmetry projectile. In Figs. 2.2 and 2.3 we see that for  $V = 2.0$  km/s the advantage decreases to about 10%, and for  $V = 2.5$  km/s it decreases to about 5%. The penetration results ( $P_i$ ) for all 8 runs are given in Table 4.

Table 4  
Penetration Results



| Run No. | V(km/s) | Pf/Lo | Proj. Mat.     |
|---------|---------|-------|----------------|
| 1       | 1.5     | 0.38  | steel          |
| 2       | 1.5     | 0.51  | "              |
| 3       | 2.0     | 0.65  | "              |
| 4       | 2.0     | 0.71  | "              |
| 5       | 2.5     | 0.80  | "              |
| 6       | 2.5     | 0.84  | "              |
| 7       | 1.5     | 0.80  | Tungsten alloy |
| 8       | 1.5     | 1.04  | "              |

Observing the plots in Appendix A, we notice substantial differences in the penetration process characteristics between the two symmetries.

The first difference has to do with lateral confinement. In Fig. 3, we show plots of material status at 1000 cycles for runs 7 and 8 (tungsten alloy into steel at 1.5 km/s). We see that while for axial symmetry a target of  $Dt/2 = 100$  mm,  $Lt = 150$  mm provides practically full confinement, for planar symmetry, even a target as large as  $Dt/2 = 280$  mm,  $Lt = 280$  is not enough, as the upper and back boundaries have moved. We also see that the lip around the crater on the front boundary is much larger for planar symmetry. It's about 5 times larger (in linear dimensions).


## TUNGSTEN INTO STEEL

### MATERIAL STATUS



(cm, gm, us)  
CYCLE 1000  
T = 1.000E+02

***Axial, 7***




(cm, gm, us)  
CYCLE 1000  
T = 1.002E+02

***Planar, 8***

**Fig. 3.** Material status for runs 7 and 8 at 1000 cycles ( $\sim 100 \mu\text{s}$ ).


The second difference has to do with crater dimensions. Both size and shape are different. As an example, we show in Fig. 4 detailed plots of the inner part of the crater in runs 7 and 8 at 1000 cycles. We see that while for axial symmetry the crater diameter is approximately constant and is about 1.8 times the projectile diameter (at 1.5 km/s) for planar symmetry the crater width is not constant, and at the entrance boundary it is about five times the projectile width. At this time, we don't have quantitative understanding or valid engineering models to account for these differences.

#### IMPACT INTO STEEL



CYCLE 1000  
T = 1.000E+02

**Axial, 7**



CYCLE 1000  
T = 1.000E+02

**Planar, 8**

Fig. 4. Crater geometry and velocity vectors for runs 7 and 8 at 1000 cycles ( $\sim 100 \mu\text{s}$ ).

## Conclusions

We used AUTODYN2D to simulate penetration of steel and tungsten alloy projectiles into steel targets for axial and planar symmetries. The purpose was to see to what extent the planar projectiles have an advantage over circular projectiles.

We found that:

- Planar projectiles penetrate more than circular projectiles at low velocities (1.5 km/s).
- Planar projectiles lose their advantage with increasing velocity.

| Velocity km/s | Advantage of<br>Planar Projectiles |
|---------------|------------------------------------|
| 1.5           | 30%                                |
| 2.0           | 10%                                |
| 2.5           | 5%                                 |

- Much larger target dimensions are needed for full confinement of planar projectiles.
- Craters created by planar projectiles are much wider and their width is not constant.

## Acknowledgments

This work was supported by the U.S. Army Armament Research, Development and Engineering Center (ARDEC) under contract DAAA21-90-D-0009.

## Appendix A

Material status and velocity vector plots for runs 1 to 8.

**Appendix A is included in only 2 copies of this report.**

Runs 1 to 8 are characterized in Table 3.




## **Appendix A1**

Plots for run No. 1

Steel projectile

Axial symmetry

1.5 km/s





MATERIAL  
STATUS

■ HYDRO  
 ■ ELASTIC  
 ■ PLASTIC  
 ■ FAILED

(CM,GM,US)  
 CYCLE 0  
 T = 0.000E+00

STEEL INTO STEEL





VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.500E-01

Scale


4.500E-01

(cm, gm, us)

CYCLE 0

T = 0.000E+00

STEEL INTO STEEL




MATERIAL  
STATUS


■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM, GM, US)  
CYCLE 200  
T = 1.952E+01

STEEL INTO STEEL



STEEL INTO STEEL




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM.GM.US)  
CYCLE 400  
T = 3.966E+01


STEEL INTO STEEL



STEEL INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM,GM,US)  
CYCLE 600  
T = 5.996E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

$8.000E-01$

Maximum  
Velocity  
 $1.456E-01$

Scale

$9.800E-01$

(cm, gm, us)


CYCLE 600

$T = 5.996E+01$

STEEL INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 800  
T = 8.057E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.456E-01

Scale


1.200E+00

(CM, GM, US)

CYCLE 800

T = 8.057E+01

STEEL INTO STEEL



MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM.GM.US)  
CYCLE 1000  
T = 1.032E+02

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.456E-01

Scale

1.300E+00

(cm, gm, us)


CYCLE 1000

T = 1.032E+02

STEEL INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 1100  
T = 1.150E+02

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.456E-01

Scale

1.400E+00

(cm, gm, us)

CYCLE 1100

T = 1.150E+02

STEEL INTO STEEL


## Appendix A2

Plots for run No. 2

Steel projectile

Axial symmetry

2.0 km/s





MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 0  
T = 0.000E+00

STEEL INTO STEEL





VELOCITY  
VECTORS

Scale



1.000E+00

Maximum  
Velocity  
2.000E-01

Scale


7.300E-01

(cm, gm, us)

CYCLE 0

T = 0.000E+00

STEEL INTO STEEL




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM,GM,US)  
CYCLE 200  
T = 1.813E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale


1.000E+00

Maximum  
Velocity  
1.994E-01

Scale

8.900E-01  
(cm, gm, us)  
CYCLE 200  
T = 1.813E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 400  
T = 3.684E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.984E-01

Scale


1.200E+00

(cm, gm, us)

CYCLE 400

T = 3.684E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 600  
T = 5.570E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.984E-01

Scale


7.600E-01

(cm, gm, us)

CYCLE 600

T = 5.570E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 800  
T = 7.488E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.984E-01

Scale

1.200E+00

(cm, gm, us)

CYCLE 800

T = 7.488E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM.GM.US)  
CYCLE 990  
T = 9.575E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.984E-01

Scale

1.900E+00

(cm, gm, us)

CYCLE 990

T = 9.575E+01

STEEL INTO STEEL


## **Appendix A3**


Plots for run No. 3

Steel projectile

Axial symmetry

2.5 km/s





VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.500E-01

Scale


1.000E+00

(cm, gm, us)

CYCLE 0

T = 0.000E+00

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 200  
T = 1.692E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.498E-01

Scale

9.600E-01

(CM, GM, US)

CYCLE 200

T = 1.692E+01

STEEL INTO STEEL




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM, GM, US)  
CYCLE 400  
T = 3.439E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.480E-01

Scale


9.800E-01

(cm, gm, us)

CYCLE 400

T = 3.439E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 600  
T = 5.201E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.480E-01

Scale


1.000E+00

(cm, gm, us)

CYCLE 600

T = 5.201E+01

STEEL INTO STEEL




MATERIAL  
STATUS

■ HYDRO  
 ■ ELASTIC  
 ■ PLASTIC  
 ■ FAILED

(CM,GM,US)  
 CYCLE 800  
 T = 7.015E+01

STEEL INTO STEEL



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.480E-01

Scale

1.300E+00

(cm, gm, us)

CYCLE 800

T = 7.015E+01

STEEL INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 925  
T = 8.362E+01

STEEL INTO STEEL



STEEL INTO STEEL




## Appendix A4

Plots for run No. 4


Steel projectile

Planar symmetry

1.5 km/s



STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.500E-01

Scale


5.800E-01

(cm, gm, us)

CYCLE 0

T = 0.000E+00

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 200  
T = 1.941E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.482E-01

Scale


1.300E+00

(cm, gm, us)

CYCLE 200

T = 1.941E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM.GM.US)  
CYCLE 400  
T = 3.958E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.457E-01

Scale


1.400E+00

(CM, GM, US)

CYCLE 400

T = 3.958E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 600  
T = 5.995E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.457E-01

Scale


1.500E+00

(cm, gm, us)

CYCLE 600

T = 5.995E+01

STEEL INTO STEEL PLANAR



MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 800  
T = 8.074E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.457E-01

Scale


1.800E+00

(CM, GM, US)

CYCLE 800

T = 8.074E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 1000  
T = 1.021E+02

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale


8.000E-01

Maximum  
Velocity  
1.457E-01

Scale

1.900E+00  
(CM.GM.U5)  
CYCLE 1000  
T = 1.021E+02

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(cm, gm, us)  
CYCLE 1400  
T = 1.450E+02

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.457E-01

Scale

2.200E+00

(cm, gm, us)

CYCLE 1400

T = 1.450E+02

STEEL INTO STEEL PLANAR




## Appendix A5


Plots for run No. 5

Steel projectile


Planar symmetry

2.0 km/s





STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
2.000E-01

Scale


6.800E-01

(cm, gm, us)

CYCLE 0

T = 0.000E+00

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(cm.gm.us)  
CYCLE 200  
T = 1.797E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.989E-01

Scale

9.700E-01

(cm, gm, us)

CYCLE 200

T = 1.797E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 400  
T = 3.672E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.948E-01

Scale

8.500E-01  
(cm, gm, us)

CYCLE 400

T = 3.672E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 600  
T = 5.567E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.948E-01

Scale

1.800E+00

(cm, gm, us)

CYCLE 600

T = 5.567E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(GM,GM,US)  
CYCLE 800  
T = 7.498E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.948E-01

Scale


8.000E-01

(cm, gm, us)

CYCLE 800

T = 7.498E+01

STEEL INTO STEEL PLANAR



MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM,GM,US)  
CYCLE 1000  
T = 9.608E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale


1.000E+00

Maximum  
Velocity  
1.948E-01

Scale

2.500E+00  
(cm, gm, us)  
CYCLE 1000  
T = 9.608E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.948E-01

Scale


7.400E-01

(cm, gm, us)

CYCLE 1000

T = 9.608E+01

STEEL INTO STEEL PLANAR



MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM.GM.US)  
CYCLE 1200  
T = 1.176E+02

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

1.000E+00

Maximum  
Velocity  
1.948E-01

Scale

2.900E+00

(cm, gm, us)

CYCLE 1200

T = 1.176E+02

STEEL INTO STEEL PLANAR



## Appendix A6

Plots for run No. 6


Steel projectile

Planar symmetry

2.5 km/s


MATERIAL  
STATUS


■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 0  
T = 0.000E+00

STEEL INTO STEEL PLANAR






VELOCITY  
VECTORS

Scale  
→  
2.000E+00

Maximum  
Velocity  
2.500E-01

Scale  
9.100E-01  
(cm, gm, us)  
CYCLE 0  
T = 0.000E+00

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 200  
T = 1.677E+01

STEEL INTO STEEL PLANAR



VELOCI  
VECTOR

Scal

2.000E

Maximu  
Veloci  
2.492E

Scal

1.300E

(CM.GM.

CYCLE 2

T = 1.6

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM.GM.US)  
CYCLE 400  
T = 3.427E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.467E-01

Scale


1.700E+00

(cm, gm, us)

CYCLE 400

T = 3.427E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(cm, gm, us)  
CYCLE 600  
T = 5.201E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.467E-01

Scale


9.100E-01

(cm, gm, us)

CYCLE 600

T = 5.201E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(cm, gm, us)  
CYCLE 800  
T = 7.079E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.467E-01

Scale


8.800E-01

(cm, gm, us)

CYCLE 800

T = 7.079E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.467E-01

Scale


3.300E+00

(cm.gm.us)

CYCLE 800

T = 7.079E+01

STEEL INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 1000  
T = 9.143E+01

STEEL INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

2.000E+00

Maximum  
Velocity  
2.467E-01

Scale

9.400E-01

(cm, gm, us)

CYCLE 1000


T = 9.143E+

STEEL INTO STEEL PLANAR



## Appendix A7

Plots for run No. 7  
Tungsten alloy projectile  
Axial symmetry  
1.5 km/s




MATERIAL  
STATUS


■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM,GM,US)  
CYCLE 0  
T = 0.000E+00

TUNGSTEN INTO STEEL



TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.500E-01


Scale

6.500E-01  
(cm, gm, us)

CYCLE 0

T = 0.000E+00

TUNGSTEN INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 200  
T = 1.928E+01

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.498E-01

Scale


8.400E-01

(cm, gm, us)

CYCLE 200

T = 1.928E+01

TUNGSTEN INTO STEEL




MATERIAL  
STATUS

 HYDRO  
 ELASTIC  
 PLASTIC  
 FAILED

(CM,GM,US)  
 CYCLE 400  
 $T = 3.923E+01$

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.460E-01

Scale

1.200E+00

(CM. GM. US)


CYCLE 400

T = 3.923E+01

TUNGSTEN INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM,GM,US)  
CYCLE 600  
T = 5.929E+01

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.460E-01

Scale

1.200E+00

(CM. GM. US)

CYCLE 600

T = 5.929E+01

TUNGSTEN INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 800  
T = 7.952E+01

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.460E-01

Scale

9.200E-01

(cm, gm, us)

CYCLE 800

T = 7.952E+01

TUNGSTEN INTO STEEL




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM.GM.US)  
CYCLE 1000  
T = 1.000E+02

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.460E-01


Scale

9.200E-01  
(cm, gm, us)

CYCLE 1000

T = 1.000E+02

TUNGSTEN INTO STEEL




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM,GM,US)  
CYCLE 1200  
T = 1.214E+02

TUNGSTEN INTO STEEL



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.460E-01


Scale

1.200E+00  
(cm, gm, us)  
CYCLE 1200  
T = 1.214E+02

TUNGSTEN INTO STEEL


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 1400  
T = 1.450E+02

TUNGSTEN INTO STEEL




TUNGSTEN INTO STEEL

## Appendix A8

Plots for run No. 8  
Tungsten alloy projectile  
Planar symmetry  
1.5 km/s


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED




(CM,GM,US)  
CYCLE 0  
T = 0.000E+00

TUNGSTEN INTO STEEL PLANAR



TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale



8.000E-01

Maximum  
Velocity  
1.500E-01

Scale


1.000E+00

(cm, gm, us)

CYCLE 0

T = 0.000E+00

TUNGSTEN INTO STEEL PLANAR




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM,GM,US)  
CYCLE 200  
T = 1.908E+01

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.491E-01

Scale


1.100E+00

(cm. gm. us)

CYCLE 200

T = 1.908E+01

TUNGSTEN INTO STEEL PLANAR




MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED

(CM.GM.US)  
CYCLE 400  
T = 3.905E+01

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-0

Maximum  
Velocity  
1.448E-0


Scale

1.800E+0  
(CM,GM,US  
CYCLE 400  
T = 3.905

TUNGSTEN INTO STEEL PLANAR


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM, GM, US)  
CYCLE 600  
T = 5.917E+6

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale

2.100E+00

(CM, GM, US)

CYCLE 600

T = 5.917E+01

TUNGSTEN INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM, GM, US)  
CYCLE 800  
T = 7.950E+01

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale

1.900E+00

(cm. gm. us)


CYCLE 800

T = 7.950E+01

TUNGSTEN INTO STEEL PLANAR


MATERIAL  
STATUS

■ HYDRO  
■ ELASTIC  
■ PLASTIC  
■ FAILED



(CM,GM,US)  
CYCLE 1000  
T = 1.002E+02

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale

1.200E+00


(CM.GM.U5)

CYCLE 1000

T = 1.002E+02

TUNGSTEN INTO STEEL PLANAR

MATERIAL  
STATUS



■ HYDRO  
■ ELASTI  
■ PLASTI  
■ FAILEI

(CM, GM, US  
CYCLE 120  
T = 1.214

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale


1.600E+00

(cm, gm, us)

CYCLE 1200

T = 1.214E+02

TUNGSTEN INTO STEEL PLANAR




MATERIAL  
STATUS

|   |         |
|---|---------|
| ■ | HYDRO   |
| ■ | ELASTIC |
| ■ | PLASTIC |
| ■ | FAILED  |

(CM.GM.US)  
CYCLE 1400  
T = 1.436E+02

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale


1.300E+00

(CM. GM. US)

CYCLE 1400

T = 1.436E+02

TUNGSTEN INTO STEEL PLANAR




MATERIAL  
STATUS

■ HYDRO  
 ■ ELASTIC  
 ■ PLASTIC  
 ■ FAILED

(CM.GM.US)  
 CYCLE 1600  
 T = 1.665E+02

TUNGSTEN INTO STEEL PLANAR



VELOCITY  
VECTORS

Scale

8.000E-01

Maximum  
Velocity  
1.448E-01

Scale

1.000E+00  
(cm.gm.us)  
CYCLE 1600  
T = 1.665E+02

TUNGSTEN INTO STEEL PLANAR

## **Appendix B Distribution List**

Administrator  
Defense Technical Information Center  
Attn: DTIC-DDA  
8725 John J. Kingman Road, Ste 0944  
Ft. Belvoir, VA 22060-6218

Director  
US Army Research Lab  
ATTN: AMSRL OP SD TA  
2800 Powder Mill Road  
Adelphi, MD 20783-1145

Director  
US Army Research Lab  
ATTN: AMSRL OP SD TL  
2800 Powder Mill Road  
Adelphi, MD 20783-1145

Director  
US Army Research Lab  
ATTN: AMSRL OP SD TP  
2800 Powder Mill Road  
Adelphi, MD 20783-1145

Director  
Army Research Laboratory  
AMSRL-CI-LP  
Technical Library 305  
APG, MD 21005-5066